DATE

TYPE

NOTES

QUICKSHIP

REV: 18 0220 1038

FL-3150A

vww.sonarayled.com

150W DELTA LED FLOOD LIGHT

INPUT VOLTAGE: AC100-277V ~ 50/60Hz **BEAM ANGLE:** 60°, 90° & 120°

POWER SUPPLY: Replaceable Driver POWER FACTOR: >0.9

LIFETIME: ≥ 50,000hrs AMBIENT OPERATING TEMPERATURE: -13°F ~ +113°F

NARAY®

Housing: The body of Delta Flood Light series is made of aluminum with an anti-corrosive coating to protect it in caustic environments, such as salt spray. The acrylic optical plate has a high-impact resistance, and the luminaire is sealed with resilient gasketing to prevent ingress.

Mounting Options: Available options include the standard yolk mount, as well as slip-fitters in order to adapt to other mounting requirements.

Electrical: The Delta Flood Light comes standard with a high-performance driver that goes from 100-277V, power factor of 90%+, internal to the fixture.

Optics: Three different beam angles are possible without any change to the physical housing structure. Also available is a shield for additional cut-off of beam angle to mitigate light trespass.

Warranty: Five (5) year warranty on entire system. For more details on warranty conditions, please contact factory.

Lumen Maintenance: The lumen packages are rated for 50,000+ hours (L₇₀).

Certifications: UL certified to UL1598. DLC listed.















ORDERING GUIDE

MODEL	WATTAGE	BEAM ANGLE	CRI	ССТ	FINISH	VOLTAGE
FL-3	150A	W	8	50	DB	U
	150A 150W	M 60 DEGREE	8 ≥80	30 3000K	DB DARK BRONZE	U 100-277V
		W 90 DEGREE		40 4000K		
		WW 120 DEGREE		50 5000K		

DIMENSIONS

Lens & Rear View Side View






	POWER	LUMENS	EFFICACY
60° BEAM ANGLE	150W	19,350 lm	129 lm/W
90° BEAM ANGLE	150W	19,350 lm	129 lm/W
120° BEAM ANGLE	150W	19,350lm	129 lm/W

ENERGY DATA

PHOTOMETRICS

90° BEAM ANGLE



Illuminance Distribution

