

Rotatable Wall Pack Installation Guide

TECHNICAL PARAMETERS

TECHNICAL PARAMETERS				
PRODUCT PHOTO				
MODEL NUMBER	WP-6040	WP-6080		
POWER CONSUMPTION	40W	80W		
OPERATING VOLTAGE	100-277V AC ~ 50/60Hz			
HOUSING MATERIAL	Aluminum			
OPERATING TEMPERATURE	-20°C ~ +50°C / -4°F ~ +122°F			
IP RATING	65			
WEIGHT	6.1			
DIMENSIONS	9.1 x 5.7 x 5.2			

SONARAY®

ATTENTION

This manual instructs the important information of installation and operation. Be sure to strictly follow the instructions before use. To ensure correct installation and operation of the product, carefully read and understand all contents of this guide. Any mechanical or electrical modifications to the product will void warranty and may cause dangerous hazards.

GENERAL MAINTENANCE

Make sure there is no power running to the luminaire when performing maintenance. The lens and the housing can be cleaned using a soft cloth without any corrosive material.

INSTALLATION PREPERATION

- 1. Take out the luminaire from the box and place it on a level platform for easy installation.
- 2. For proper operation, a qualified electrician should perform the installation.
- 3. Ensure the normal ambient temperature of the installation location is between -25°C ~ +45°C.
- 4. Ensure the voltage of the luminaire is capatable with the onsite voltage before installation.
- 5. Any luminaire with damaged power cord should not be installed.

Note: The power must be cut off before installation.

INSTALLATION DIAGRAM

Cut holes on the wall according to the template.	2. Insert the rubber plugs into the holes.	3. Align the mounting bracket with the holes and tighten the screws.
109		
Make the wiring connection and go through the mounting bracket hole.	5. Fix the luminaire on the bracket and tighten the bottom screws.	Tighten the remaining screws to complete the installation.
	•	

TROUBLESHOOTING

SITUATION	POSSIBLE REASON	POSSIBLE SOLUTION
LED DOES NOT LIGHT UP	Incorrect input wiring	Confirm wire colors
	No power to the luminaire	Recycle power or check power connection
	Incorrect voltage	Confirm voltage
LED FLICKER	Poor power connection	Check power connection
	Input voltage fluctation	Confirm voltage