

## CSAL-1000

### FEATURES

- Gray finish
- Wide lighting distribution
- Wall Arm Mounting Bracket
- Adjustable Wattage and CCT
- 4,375 - 8,125 lumens
- 125 lm/W
- IP65
- 5 Year Warranty



### APPLICATIONS

- Commercial • Yards & Loading Docks • Walkway • Area Lighting • Recreational

### ORDERING GUIDE

SERIES	WATTAGE	BEAM ANGLE	CRI	CCT	FINISH	VOLTAGE
CSAL-1	065 35W / 50W / 65W	WW 140 DEGREE	7 ≥70	50 3000K / 4000K / 5000K	GRY GRAY	U 100-277V

LED SPECIFICATION			5000K		WEIGHT (lbs.)	CERTIFICATION
MODEL	WATTS	OPTIC	LUMENS	EFFICACY		
CSAL-1065	35	T3	4,375	125 lm/W	3.31	DLC, UL
	50	T3	6,250	125 lm/W		
	65	T3	8,125	125 lm/W		

### SPECIFICATIONS

#### CONSTRUCTION

Cold forged Aluminum Housing and Polycarbonate lens suitable for all environments. Gray finish available. The unit is sealed with resilient gasketing to prevent ingress.

#### INSTALLATION

Integrated Wall Arm Mounting Bracket.

#### WARRANTY

All CSAL-1000 products come with a limited Five (5) Year Warranty. For more information regarding the warranty please contact the factory at (844) 202-5606 or email Customer Service at LEDCustService@dascom.com.

#### ELECTRICAL

Luminaire is paired with a high performance 100-277V AC driver. 50/60 Hz. Power Factor >.9 with THD <.2. A minimum CRI of 70 is provided in 3000K, 4000K, and 5000K color temperatures.

#### OPTICS

Wide distribution of 140° beam spread.

#### CERTIFICATIONS

DesignLights Consortium Standard qualified product for all Models UL certified to UL1598. IP65 Rated. Ambient Operating Temperature: -40°C ~ +45°C / -40°F ~ +113°F