

CSFL-1000

FEATURES

- Dark Bronze finish
- Wide lighting distribution
- Yoke Mount Bracket
- 3,900 - 6,500 lumens
- 130 lm/W
- IP65
- 5 Year Warranty



APPLICATIONS

- Area Lighting • Wall Washing • Signage • Recreational

ORDERING GUIDE

SERIES	WATTAGE	BEAM ANGLE	CRI	CCT	FINISH	VOLTAGE
CSFL-1	030 30W 050 50W	WW 120 DEGREE	8 ≥80	50 5000K	DB DARK BRONZE	U 100-277V

LED SPECIFICATION			5000K		WEIGHT (lbs.)	CERTIFICATION
MODEL	WATTS	OPTIC	LUMENS	EFFICACY		
CSFL-1030	30	WW	3,900	130 lm/W	2.35	DLC, ETL
CSFL-1050	50	WW	6,500	130 lm/W	3.81	DLC, ETL

SPECIFICATIONS

CONSTRUCTION

Die-cast Aluminum Housing and Polycarbonate lens suitable for all environments. The unit is sealed with resilient gasketing to prevent ingress.

INSTALLATION

Rotatable Yoke Mount standard.

WARRANTY

All CSFL-1000 products come with a limited Five (5) Year Warranty. For more information regarding the warranty please contact the factory at (844) 202-5606 or email Customer Service at LEDCustService@dascom.com.

ELECTRICAL

Luminaire is paired with a high performance 100-277V, 50/60 Hz driver. Power Factor >.9 with THD <.20%. A minimum CRI of 80 is standard in 5000K color temperature.

OPTICS

Wide distribution of 120 degrees.

CERTIFICATIONS

DesignLights Consortium Standard qualified product for all Models. ETL certified to UL1598. IP65 Rated. Ambient Operating Temperature: -40°C ~ +45°C / -40°F ~ +113°F