

## CSFL-2000

### FEATURES

- Dark Bronze finish
- Wide lighting distribution
- Yoke Mount Bracket
- 21,750 - 34,800 lumens
- 145 lm/W
- IP66
- 5 Year Warranty



### APPLICATIONS

- Area Lighting • Wall Washing • Signage • Recreational

### ORDERING GUIDE

SERIES	WATTAGE	BEAM ANGLE	CRI	CCT	FINISH	VOLTAGE
CSFL-2	150 150W 200 200W 240 240W	WW 120 DEGREE	7 ≥70	50 5000K	DB DARK BRONZE	U 100-277V

LED SPECIFICATION			5000K		WEIGHT (lbs.)	CERTIFICATION
MODEL	WATTS	OPTIC	LUMENS	EFFICACY		
CSFL-2150	150W	WW	21,750	145 lm/W	9.47	DLC, ETL
CSFL-2200	200W	WW	29,000	145 lm/W	11.24	DLC, ETL
CSFL-2240	240W	WW	34,800	145 lm/W	14.33	DLC, ETL

### SPECIFICATIONS

#### CONSTRUCTION

Die-cast Aluminum Housing and Polycarbonate lens suitable for all environments. The unit is sealed with resilient gasketing to prevent ingress.

#### INSTALLATION

Rotatable Yoke Mount standard.

#### WARRANTY

All CSFL-2000 products come with a limited Five (5) Year Warranty. For more information regarding the warranty please contact the factory at (844) 202-5606 or email Customer Service at LEDCustService@dascom.com.

#### ELECTRICAL

Luminaire is paired with a high performance 100-277V, 50/60 Hz driver. Power Factor >.9 with THD <.20%. A minimum CRI of 70 is standard in 5000K color temperature.

#### OPTICS

Wide distribution of 120 degrees.

#### CERTIFICATIONS

DesignLights Consortium Standard qualified product for all Models. ETL certified to UL1598. IP65 Rated. Ambient Operating Temperature: -40°C ~ +45°C / -40°F ~ +113°F