

CSHB-1000

FEATURES

- Black or White finish
- Wide lighting distribution
- Open Hook Mounting
- 16,000 - 38,400 lumens
- 160 lm/W
- IP65
- Dimmable
- 5 Year Warranty



APPLICATIONS

• Gymnasium • Warehouse • Factory • Showroom • Recreational



ORDERING GUIDE

SERIES	WATTAGE	BEAM ANGLE	CRI	CCT	FINISH	VOLTAGE
CSHB-1	100 100W 150 150W 200 200W 240 240W	WW 120 DEGREE	8 ≥80	50 5000K	BLK BLACK WHT ¹ WHITE	U 100-277V H ² 277-480V

¹ Not available for the 100W Wattage model

² Not available for the 100W Wattage or White Finish models

LED SPECIFICATION			5000K		WEIGHT (lbs.)	CERTIFICATION
MODEL	WATTS	OPTIC	LUMENS	EFFICACY		
CSHB-1100	100	WW	16,000	160 lm/W	6.39	DLC, ETL
CSHB-1150	150	WW	24,000	160 lm/W	9.03	DLC, ETL
CSHB-1200	200	WW	32,000	160 lm/W	11.68	DLC, ETL
CSHB-1240	240	WW	38,400	160 lm/W	11.68	DLC, ETL

SPECIFICATIONS

CONSTRUCTION

Die-cast Aluminum Housing and Polycarbonate lens suitable for all environments. Black or White finishes available. The unit is sealed with resilient gasketing to prevent ingress.

INSTALLATION

Unit mounts using an open hook loop mount for easy installation.

WARRANTY

All CSHB-1000 products come with a limited Five (5) Year Warranty. For more information regarding the warranty please contact the factory at (844) 202-5606 or email Customer Service at LEDCustService@dascom.com.

ELECTRICAL

Luminaire is paired with a high performance 100-277V, 50/60 Hz driver. Power Factor >.9 with THD <.20%. High Voltage 480V driver available for selected models. A minimum CRI of 80 is standard in 5000K color

OPTICS

Wide distribution of 120 degrees.

CERTIFICATIONS

DesignLights Consortium Standard qualified product for all Models. ETL certified to UL1598. IP65 Rated. Ambient Operating Temperature: -40°C ~ +45°C / -40°F ~ +113°F