

CSHB-2000

FEATURES

- White finish
- Wide lighting distribution
- Recessed Mounting
- 21,450 - 39,000 lumens
- 130 lm/W
- IP65
- Dimmable
- 5 Year Warranty



APPLICATIONS

- Gymnasium • Warehouse • Factory • Showroom • Recreational

ORDERING GUIDE

SERIES	WATTAGE	BEAM ANGLE	CRI	CTT	FINISH	VOLTAGE
CSHB-2	165 165W 220 220W 300 300W	WW 120 DEGREE	8 ≥80	50 5000K	WHT WHITE	U 100-277V

LED SPECIFICATION			5000K		WEIGHT (lbs.)	CERTIFICATION
MODEL	WATTS	OPTIC	LUMENS	EFFICACY		
CSHB-2165	165	WW	21,450	130 lm/W	7.82	DLC, UL
CSHB-2220	220	WW	28,600	130 lm/W	7.82	DLC, UL
CSHB-2300	300	WW	39,000	130 lm/W	8.44	DLC, UL

SPECIFICATIONS

CONSTRUCTION

Die-cast Aluminum Housing and Polycarbonate lens suitable for all environments. White finish. The unit is sealed with resilient gasketing to prevent ingress.

INSTALLATION

Unit mounts by Hanging or Surface Mount kits.

WARRANTY

All CSHB-2000 products come with a limited Five (5) Year Warranty. For more information regarding the warranty please contact the factory at (844) 202-5606 or email Customer Service at LEDCustService@dascom.com.

ELECTRICAL

Luminaire is paired with a high performance 100-277V, 50/60 Hz driver. Power Factor >.9 with THD <.20%. A minimum CRI of 80 is standard in 5000K color temperature. All CSHB-2000 units are 0-10V Dimmable.

OPTICS

Wide distribution of 120 degrees.

CERTIFICATIONS

DesignLights Consortium Standard qualified product for all Models
UL certified to UL1598.
IP65 Rated.
Ambient Operating Temperature: -40°C ~ +45°C / -40°F ~ +113°F