

CSHM-1000

FEATURES

- Dark Bronze finish
- Narrow lighting distribution
- Yoke Mount Bracket
- 66,000 - 132,000 lumens
- 110 lm/W
- IP65
- Dimmable
- 5 Year Warranty



APPLICATIONS

• High Mast and Contour Lighting • Service Center • Shipyard • Airport

ORDERING GUIDE

SERIES	WATTAGE	BEAM ANGLE	CRI	CCT	FINISH	VOLTAGE
CSHM-1	600 600W 200 1200W	M 38 DEGREE	7 ≥70	50 5000K	DB DARK BRONZE	U 90-277V

LED SPECIFICATION			5000K		WEIGHT (lbs.)	CERTIFICATION
MODEL	WATTS	OPTIC	LUMENS	EFFICACY		
CSHM-1600	600	M	66,000	110 lm/W	35.71	DLC, UL
CSHM-1200	1200	M	132,000	110 lm/W	66.75	DLC, UL

SPECIFICATIONS

CONSTRUCTION

Pure 1070 Aluminum Housing with anti-corrosive finish suitable for all environments. The unit is sealed with resilient gasketing to prevent ingress.

INSTALLATION

Standard Yoke Mount bracket.

WARRANTY

All CSHM-1000 products come with a limited Five (5) Year Warranty. For more information regarding the warranty please contact the factory at (844) 202-5606 or email Customer Service at LEDCustService@dascom.com.

ELECTRICAL

Luminaire is paired with a high performance 90-277V AC driver. 50/60 Hz. Power Factor >.9 with THD <.2. A minimum CRI of 70 is provided in 5000K color temperatures. Unit is dimmable.

OPTICS

Narrow distribution of 38° beam spread.

CERTIFICATIONS

DesignLights Consortium Standard qualified product for all Models
 UL certified to UL1598.
 IP65 Rated.
 Ambient Operating Temperature: -35°C ~ +50°C / -31°F ~ +122°F