

CSPT-1000

FEATURES

- White finish
- Wide lighting distribution
- Surface Mounting
- 19,500 lumens
- 130 lm/W
- IP65
- Dimmable
- 5 Year Warranty



APPLICATIONS

- Gas Station • Service Center • Parking Garage

ORDERING GUIDE

SERIES	WATTAGE	BEAM ANGLE	CRI	CCT	FINISH	VOLTAGE
CSPT-1	150 150W	WW 120 DEGREE	7 ≥75	50 5000K	WHT WHITE	U 90-277V

LED SPECIFICATION			5000K		WEIGHT (lbs.)	CERTIFICATION
MODEL	WATTS	OPTIC	LUMENS	EFFICACY		
CSPT-1150	150	WW	19,500	130 lm/W	12.84	DLC, UL

SPECIFICATIONS

CONSTRUCTION

Die-cast Aluminum Housing and a clear Polycarbonate lens suitable for all environments. The unit is sealed with resilient gasketing to prevent ingress.

INSTALLATION

Surface Mount.

WARRANTY

All CSPT-1000 products come with a limited Five (5) Year Warranty. For more information regarding the warranty please contact the factory at (844) 202-5606 or email Customer Service at LEDCustService@dascom.com.

ELECTRICAL

Luminaire is paired with a high performance 100-277V AC driver. 50/60 Hz. Power Factor >.9 with THD <.2. A minimum CRI of 70 is provided in 5000K color temperatures.

OPTICS

Wide distribution of 120° beam spread.

CERTIFICATIONS

DesignLights Consortium Standard qualified product for all Models
 UL certified to UL1598.
 IP65 Rated.
 Ambient Operating Temperature: -40°C ~ +45°C / -40°F ~ +113°F