

## HB-5125

### 125W LINEAR HIGH BAY

**BEAM ANGLE:** 120°

**INPUT VOLTAGE:** AC100-277V ~ 50/60Hz

**POWER SUPPLY:** Integral Driver

**POWER FACTOR:** >0.9

**LIFETIME:** ≥ 50,000hrs

**AMBIENT OPERATING TEMPERATURE:** -13°F ~ +113°F



**Housing:** The body of the linear high bay is made of a few extruded aluminum and polycarbonate pieces, making it both a rugged and resilient luminaire capable of working in demanding environments. The luminaire is sealed with resilient gasketing to prevent ingress.

**Mounting Options:** Pendant mounting with aircraft cable is standard. If a different mounting option is required please contact the factory.

**Electrical:** The Linear High Bay comes standard with a high-performance driver designed in-house that goes from 100-277V, power factor of 90%+, internal to the fixture. Surge protection up to 80 amperes.

**Warranty:** Five (5) year warranty on entire system. For more details on warranty conditions, please contact factory.

**Lumen Maintenance:** The lumen packages are rated for 50,000+ hours (L<sub>70</sub>).

**Certifications:** ETL certified.



Double Unit shown here

## ORDERING GUIDE

MODEL	WATTAGE	BEAM ANGLE	CRI	CCT	FINISH	VOLTAGE	MOUNTING ACCESSORIES
HB-5	125	WW	8		S	U	
	125 125W	WW 120 DEGREE	8 ≥ 80	40 4000K 50 5000K	S SILVER	U 100-277V	M1 MOUNTING FOR 1 UNIT M2 MOUNTING FOR 2 UNITS M3 MOUNTING FOR 3 UNITS

## DIMENSIONS



## ENERGY DATA

	POWER	LUMENS	EFFICACY
SINGLE UNIT	125W	17,125 lm	137 lm/W
DOUBLE UNIT	250W	34,250 lm	137 lm/W
TRIPLE UNIT	375W	51,375 lm	137 lm/W

## PHOTOMETRICS

Light Distribution Curve

