

MB-3029

ADJUSTABLE 2 x 2 LED FLAT PANEL

BEAM ANGLE: 120°

INPUT VOLTAGE: AC100-277V ~ 50/60Hz

POWER SUPPLY: Integral Driver

POWER FACTOR: >0.95

LIFETIME: ≥ 50,000hrs

AMBIENT OPERATING TEMPERATURE: -4°F ~ +122°F



Housing: Durable aluminum with a seamless frame for zero light leak around the corners.

Mounting Options: Surface Mount and Dry Wall kits available as well as Aircraft Cable.

Electrical: The LED Flat Panel comes standard with a high-performance driver that goes from 100-277V, power factor of 95%+, internal to the fixture. Dimming 0-10V standard. Optional 90 minute battery backup available.

Optics: Polycarbonate lens. Back-lit design for a glare-free output.

Warranty: Five (5) year warranty on entire system. For more details on warranty conditions, please contact factory.

Lumen Maintenance: The lumen packages are rated for 50,000+ hours (L70).

Certifications: UL listed. IP40.



ORDERING GUIDE

MODEL	WATTAGE	BEAM ANGLE	CRI	CCT	VOLTAGE	MOUNTING	OPTIONS
MB-3	029	WW	8	50	U		
	029 15W / 19W / 24W / 29W	WW 120 DEGREE	8 ≥80	50 35K / 40K / 50K	U 100-277V	SM Surface Mount Kit DW Dry Wall Kit AC Aircraft Cable	EM Battery Backup

ENERGY DATA

	POWER	LUMENS	EFFICACY
5000K	15W	1,950 lm	130 lm/W
	19W	2,470 lm	130 lm/W
	24W	3,120 lm	130 lm/W
	29W	3,770 lm	130 lm/W