

ST-3060A

60W DELTA LED STREET LIGHT

BEAM ANGLE: Type III

INPUT VOLTAGE: AC100-277V ~ 50/60Hz

POWER SUPPLY: Replaceable Driver

POWER FACTOR: >0.9

LIFETIME: ≥ 50,000hrs

OPERATING TEMPERATURE: -13°F ~ +113°F



IK08

Housing: The body of Delta Street Light series is made of aluminum with an anti-corrosive coating to protect it in caustic environments, such as salt spray. The acrylic optical plate has a high-impact resistance, and the luminaire is sealed with resilient gasketing to prevent ingress.

Mounting Options: Available options include a 2-3/8" adjustable pole mount, as well as slip-fitters in order to adapt to other mounting requirements. Pole arms are not included.

Electrical: The Delta Street Light comes standard with a high-performance, replaceable driver that goes from 100-277V, power factor of 90%+. The Easy Interchange System (EIS) allows for simple and easy field replaceability of the driver.

Warranty: Five (5) year warranty on entire system. For more details on warranty conditions, please contact factory.

Lumen Maintenance: The lumen packages are rated for 50,000+ hours (L₇₀).

Certifications: UL certified to UL1598.




With **EIS**

ORDERING GUIDE



MODEL	WATTAGE	BEAM ANGLE	CRI	CCT	FINISH	VOLTAGE
ST-3	060A	T3	8		DB	U
	060A 60W (with EIS)	T3 TYPE III	8 ≥80	30 3000K 40 4000K 50 5000K	DB DARK BRONZE	U 100-277V

DIMENSIONS

ST-3060A: Side View



ST-3060A: Top & Lens View



ENERGY DATA

	POWER	LUMENS	EFFICACY
TYPE III DIST.	60W	7200 lm	120 lm/W

PHOTOMETRICS

TYPE III DISTRIBUTION

