

## WP-5080 Wall Pack

### 80W NON CUTOFF LED WALL PACK

**BEAM ANGLE:** 120°

**INPUT VOLTAGE:** AC100-277V ~ 50/60Hz

**POWER SUPPLY:** Integral Driver

**POWER FACTOR:** >0.9

**LIFETIME:** ≥ 50,000hrs

**AMBIENT OPERATING TEMPERATURE:** -13°F ~ +113°F



**Housing:** Durable cast-aluminum housing with a powder coat finish. With an IP rating of 65, the housing is tightly sealed to prevent moisture and contaminants from entering the fixture. Dark bronze is the standard color finish. Optional photocell is available.

**Mounting Options:** Fixtures are designed to mount on exterior wall surfaces.

**Electrical:** The LED Wall Pack comes standard with a high-performance driver designed in-house that goes from 100-277V, power factor of 90%+, internal to the fixture. Surge protection up to 80 amperes.

**Optics:** Polycarbonate lens standard for even non-cutoff distribution. Also available is a glare shield for optional cut-off of beam angle to mitigate light trespass.

**Warranty:** Five (5) year warranty on entire system. For more details on warranty conditions, please contact factory.

**Lumen Maintenance:** The lumen packages are rated for 50,000+ hours (L<sub>70</sub>).

**Certifications:** UL certified to UL1598 (Suitable for Wet Locations). DLC listed.




## ORDERING GUIDE


MODEL	WATTAGE	BEAM ANGLE	CRI	CCT	FINISH	VOLTAGE	OPTIONS
WP-5	080	WW	8	50	DB	U	
	080 80W	WW 120 DEGREE	8 ≥80	50 5000K	DB DARK BRONZE	U 100-277V	PC Photocell BB Battery Backup SH Shield

## DIMENSIONS

Lens View



Side View



## ENERGY DATA

	POWER	LUMENS	EFFICACY
5000K	80W	10,640 lm	133 lm/W